

40 Amp 4 pole 5Y6 Heavy Duty NEMA Contactor

944120 120 VAC Coil

SPECIFICATIONS

AC 40A. General purpose 600V

Max 2 HP Single Phase at 115V, 10 HP at 230V,
15 HP Three Phase at 480V

DC 30A 24VDC

Coil:120VAC, 67VA inrush, 15VA sealed

4 Normally Open (N.O.) main contacts

UL Listed

Weight: 1.08 lb (0.55 kg)

Coil 110 - 120 VAC

Dimensions Height 3.77 In., Width 3.00", Depth 3.00 In



934120



934120

Replaces the following manufacturer's products
OEM numbers are used for reference only,

OEM # cleveland 101899 hatco 02.01.017.00

GE/Hobart xnc6x130/346466-15 hatco 02-01-017

Hatco 02-01-017-00 hatco 02.01.017 hobart 346466-15
middleby marshall a25788

vulcan hart 111497d1 hartland 101899

GE CR353AD4BA1 - Replaced by Eaton / Cutler Hammer C25ENF440A

ABB, DP40C4P Square D 8910DPA44V02

Siemens 45EG20AJ

Compliance:

CSA C22.2 No. 14, EN 60947-4-1, EN 60947-5-1, IEC 947-2, IEC 60947-4-1, IEC 60947-5-1, UL 508, VDE 0660

