



ELECTRODEPOT

Contactor, IEC,

120VAC, 3P, 18A

Part # 931810

- Rated Operational Current : 18A;lth : 32A;Ui : 660V

Technical Specifications

- Contactor 660V
- Contactor Type IEC
- Full Load Amps-Inductive 18
- Full Load Amps-Resistive 32
- Number of Poles 3
- Coil Volts 120VAC
- Hz 50/60
- Action Non reversing
- Enclosure Type Open
- Auxiliary Contact Form 1NC/1NO
- Coil inrush 70VA, Sealed 7.5VA
- 1 HP @ 1 Phase - 120V
- 3 HP @ 1 Phase - 230V
- 5 HP @ 3 Phase - 208V
- 5 HP @ 3 Phase - 230V
- 10 HP @ 3 Phase - 480V
- 15HP @ 3 Phase - 575V
- Height 3.50"
- Width 1.77"
- Depth 3.02"
- Standards CE,
- Base or DIN 35mm mount

Wiring:

Solid Conductor: 25 mm² Max torque 0.6 Nm

Stranding Conductor: 16 mm², Max torque 0.6 Nm

Compliance:

CSA C22.2 No. 14, EN 60947-4-1, EN 60947-5-1, IEC 947-2, IEC 60947-4-1, IEC 60947-5-1, UL 508,